



ROYAL BATHS MANUFACTURING CO., LTD.

OPERATING INSTRUCTIONS

1. Fill tub with water 2" to 4" above hydro-jets.
2. **DO NOT RUN WITHOUT WATER AT SUGGESTED LEVEL IN TUB FIRST.**
3. Adjust the two (2) air controls at top of tub on each side. This regulates movement and velocity of water. Adjust the six (6) hydro-jets to maximize the benefits of the magic **bubbles** to relax away weariness and tension.
4. Step in and enjoy the luxury of whirlpool bathing.
5. Cleaning is recommended once a month. To clean, just use 1 cup of chlorine bleach or vinegar, and run for five minutes with hot water and drain. When drained, fill with cold water and run the system for another five minutes. To conserve water, when you have finished a hot bath, just add the bleach or vinegar to that water, and then follow the above listed directions.
6. **DO NOT USE** abrasive cleaners as these may scratch and dull the surface of the unit. To clean the unit after installation, use warm water and liquid detergent such as Glass Plus, Mr. Clean or Top Job.

Clean grease, oil, paint and ink stains with isopropyl (rubbing) alcohol. Adhesive residue can be easily and safely removed by properly using products like WD40®, Liftoff®, GooGone®, or DeSolv-It®. Plaster can be removed by scraping with a sharpened soft wood stick. **DO NOT USE** metal scrapers, wire brushes, scouring type pads or other metal tools. One of the power type detergents, such as Spic and Span, may be used dry on a damp cloth to provide mild abrasive action to the residual plaster.

Dulled areas may be restored by using an auto polishing compound followed by a light application of acrylic car polish. Light scratches can be quickly and easily repaired by hand sanding with 600 grit wet/dry sandpaper then using the polishing compound and an acrylic car polish. Deep scratches are also repairable, however, it is recommended that professional help be obtained.

This literature supersedes all previous printed material from Royal Baths Manufacturing Co.